

GF 3600

CARICATORE FORESTALE

Via 1° Maggio, 32/36


25010 ISORELLA (BS) Italia

Tel. +39.030.9529199

Fax +39.030.9529284

www.tecnodraulic.com

info@tecnodraulic.com



GF 3600

CARATTERISTICHE TECNICHE	TECHNICAL FEATURES	DESCRIPTION TECHNIQUE	TECHNISCHE DATEN	DESCRIPCION TECNICA	
Capacità di sollevamento	Lifting torque netto	Capacité de levage	Hubmoment netto	Capacidad de elevación	7,4 kNm
Potenza richiesta	Requested power	Puissance requise	Leistungsbedarf	Potencia necesaria	8-10 kw
Portata consigliata pompa	Recommended oil flow	Débit d'huile conseillé	Empf. Durchflussmenge	Caudal de bomba recomendado	15 lt/min
Pressione di esercizio	Working pressure	Pression de service	Arbeitsdruck	Presión de trabajo	180 bar
Pressione massima di rotazione	Max. slewing pressure	Pression max. de rotation	max. Schwenkdruck	Presión máxima de giro	150 bar
Capacità di rotazione	Slewing torque netto	Capacité de rotation	Schwenkmoment netto	Capacidad de giro	4 kNm
Angolo di rotazione	Slewing angle	Angle de rotation	Schwenkwinkel	Angulo de giro	380° e ritorno
Peso caricatore (senza attrezzatura)	Weight (without equipment)	Poids (sans équipement)	Gewicht (ohne Ausrüstung)	Peso (sin equipo)	380 Kg

Con riserva di modifiche. We reserve the right to introduce changes without prior notice. Droit de modification sans préavis réservé. Konstruktionsänderungen vorbehalten. Reservado el derecho de modificaciones sin preaviso.

